

IN THE CLAIMS

Please amend the claims to read as follows:

Listing of Claims

1. (Withdrawn) A hydrogen generator comprising:

a reformer configured to conduct a steam reforming reaction to reform a material to generate a reformed gas containing carbon monoxide, water and hydrogen;

a shift converter configured to conduct a shift reaction using the carbon monoxide and steam in the reformed gas;

a water supply device configured to supply the water to said reformer;

a material feed device configured to feed the material to said reformer; and

a reformed gas temperature adjusting device configured to cool and heat the reformed gas flowing into said shift converter; and

a controller which is configured to count the number of times of start up and/or stop of said hydrogen generator and to control said water supply device and said material feed device to increase a temperature or a S/C ratio of the reformed gas flowing in said shift converter according to the counted number of times of start up and/or stop or is configured to count the number of times of start-up and/or stop of said hydrogen generator and to control said reformed gas temperature adjusting device to increase a temperature of the reformed gas according to the counted number of times of start-up and/or stop.

2-3. (Cancelled).

4. (Withdrawn) The hydrogen generator according to claim 1, further comprising:
a reformed gas temperature adjusting device configured to cool and heat the reformed gas flowing into said shift converter; wherein

said controller counts an accumulated operation time of said hydrogen generator, and controls said reformed gas temperature adjusting device to increase the temperature of the reformed gas according to the counted number of times of start up and/or stop and the counted accumulated operation time of said hydrogen generator.

5. (Withdrawn) The hydrogen generator according to claim 1, wherein said controller counts an accumulated operation time of said hydrogen generator, and controls said water supply device and said material feed device to increase the S/C ratio of the reformed gas according to the counted number of times of start up and/or stop and the counted accumulated operation time of said hydrogen generator.

6. (Withdrawn) The hydrogen generator according to claim 1, further comprising:
a temperature detector configured to detect the temperature of the reformed gas at an inlet of said shift converter from which the reformed gas flows into said shift converter;

wherein, at re start up after stop of said hydrogen generator, said controller obtains a detected value from said temperature detector, compares the detected value to a temperature condition of water condensation, and counts the number of times of start up and/or stop of said

hydrogen generator when the detected value matches the temperature condition of water condensation.

7. (Withdrawn) The hydrogen generator according to claim 2,
wherein said controller pre stores controlled temperature data such that a controlled temperature corresponds to the number of times of start up and/or stop;
and wherein said controller selects the controlled temperature from the controlled temperature data according to the counted number of times of start up and/or stop and controls said reformed gas temperature adjusting device so that the temperature of the reformed gas becomes the selected controlled temperature.

8. (Withdrawn) The hydrogen generator according to claim 3,
wherein said controller pre stores controlled S/C ratio data such that a controlled S/C ratio corresponds to the number of times of start up and/or stop;
and wherein said controller selects the controlled S/C ratio from the controlled S/C ratio data according to the counted number of times of start up and/or stop and controls said water supply device and said material feed device so that the S/C ratio of the reformed gas becomes the selected controlled S/C ratio.

9. (Withdrawn) The hydrogen generator according to claim 7,
wherein said controller counts the accumulated operation time of said hydrogen generator;

and wherein said controller selects the controlled temperature from the controlled temperature data according to the counted number of times of start up and/or stop and the counted accumulated operation time, and controls said reformed gas temperature adjusting device so that a detected temperature from said temperature detector becomes the selected controlled temperature.

10. (Withdrawn) The hydrogen generator according to claim 8,
wherein said controller counts the accumulated operation time of said hydrogen generator;

and wherein said controller selects a controlled S/C ratio from the controlled S/C ratio data according to the counted number of times of start up and/or stop and the counted accumulated operation time, and controls said water supply device and said material feed device so that the S/C ratio of the reformed gas becomes the selected controlled S/C ratio.

11. (Withdrawn) The hydrogen generator according to claim 9, wherein said controller stores controlled temperature data such that the controlled temperature corresponds to the number of times of start up and/or stop and the accumulated operation time, selects the controlled temperature from the controlled temperature data according to the counted number of times of start up and/or stop and the counted accumulated operation time, and controls said reformed gas temperature adjusting device so that the detected temperature from said temperature detector becomes the selected controlled temperature.

12. (Withdrawn) The hydrogen generator according to claim 10, wherein said controller stores controlled S/C ratio data such that the controlled S/C ratio corresponds to the number of times of start up and/or stop and the accumulated operation time, selects the controlled S/C ratio from the controlled S/C ratio data according to the counted number of times of start up and/or stop and the counted accumulated operation time, and controls said water supply device and said material feed device so that the S/C ratio of the reformed gas becomes the selected controlled S/C ratio.

13. (Withdrawn) The hydrogen generator according to claim 7, further comprising:
an oxidizing agent supply device configured to add an oxidizing agent to the reformed gas that has flowed through said shift converter; and

a carbon monoxide selective oxidation device configured to conduct selective oxidation using the carbon monoxide and the oxidizing agent in the reformed gas;

wherein said controller pre stores carbon monoxide concentration data such that a carbon monoxide concentration of the reformed gas after the shift reaction at the controlled temperature is associated with the controlled temperature;

and wherein said controller selects a carbon monoxide concentration corresponding to the selected controlled temperature from the carbon monoxide concentration data, calculates a controlled oxidizing agent flow rate from a reformed gas flow rate and the selected carbon monoxide concentration, and controls said oxidizing agent supply device to add the oxidizing agent to the reformed gas with the controlled oxidizing agent flow rate.

14. (Withdrawn) The hydrogen generator according to claim 8, further comprising:
an oxidizing agent supply device configured to add an oxidizing agent to the reformed gas that has flowed through said shift converter; and
a carbon monoxide selective oxidation device configured to conduct selective oxidation using the carbon monoxide and the oxidizing agent in the reformed gas;
wherein said controller pre stores carbon monoxide concentration data such that a carbon monoxide concentration of the reformed gas after the shift reaction in the controlled S/C ratio is associated with the controlled S/C ratio;
and wherein said controller selects a carbon monoxide concentration corresponding to the selected controlled S/C ratio from the carbon monoxide concentration data, calculates a controlled oxidizing agent flow rate from a reformed gas flow rate and the selected carbon monoxide concentration, and controls said oxidizing agent supply device to add the oxidizing agent to the reformed gas with the controlled oxidizing agent flow rate.

15. (Withdrawn) The hydrogen generator according to claim 2, wherein said reformed gas temperature adjusting device is configured to adjust the temperature of the reformed gas by water cooling the reformed gas in a reformed gas passage through which said reformer and said shift converter communicate with each other, and water that has cooled the reformed gas is supplied to said reformer.

16. (Withdrawn) A fuel cell system comprising:
a fuel cell; and

a hydrogen generator according to claim 1;

said hydrogen generator being configured to supply as a fuel gas, to said fuel cell, a reformed gas that has flowed through said shift converter, and being configured to start up and stop in association with an operation of said fuel cell and to adjust a supply amount of the reformed gas according to a power output of said fuel cell;

wherein said controller of said hydrogen generator is configured to count the number of times of start up and/or stop of said fuel cell.

17. (Withdrawn) A fuel cell system comprising:

a fuel cell; and

a hydrogen generator according to claim 9;

said hydrogen generator being configured to supply as a fuel cell, to said fuel cell, a reformed gas that has flowed through said shift converter, and being configured to start up and stop in association with an operation of said fuel cell and to adjust a supply amount of the reformed gas according to a power output of said fuel cell;

wherein said controller of said hydrogen generator is configured to count the number of times of start up and/or stop of said fuel cell and an accumulated operation time of said fuel cell.

18. (Withdrawn) A fuel cell system comprising:

a fuel cell; and

a hydrogen generator according to claim 10;

said hydrogen generator being configured to supply as a fuel gas, to said fuel cell, a reformed gas that has flowed through said shift converter, and being configured to start up and stop in association with an operation of said fuel cell and to adjust a supply amount of the reformed gas according to a power output of said fuel cell;

wherein said controller of said hydrogen generator is configured to count the number of times of start up and/or stop of said fuel cell and an accumulated operation time of said fuel cell.

19. (Withdrawn) The hydrogen generator according to claim 1, wherein said controller includes an output device that displays or outputs the counted number of times of start up and/or stop.

20. (Withdrawn) The hydrogen generator according to claim 1, further comprising:
a carbon monoxide concentration detector configured to detect a carbon monoxide concentration of the reformed gas that has flowed through said shift converter;

wherein said controller pre stores an upper limit value of the carbon monoxide concentration of the reformed gas;

and wherein said controller compares a detected value from said carbon monoxide concentration detector to the upper limit value, and increases the temperature or the S/C ratio of the reformed gas flowing in said shift converter when the detected value is larger than the upper limit value.

21. (Currently Amended) A method of operating a hydrogen generator ~~including a reformer configured to conduct a steam reforming reaction to reform a material to generate a reformed gas containing carbon monoxide, water and hydrogen; a shift converter configured to conduct a shift reaction using the carbon monoxide and steam in the reformed gas; a water supply device configured to supply the water to said reformer; and a material feed device configured to feed the material to said reformer;~~ comprising the steps of:

- (a) heating a reformer by a heater;
- (b) causing a steam reforming reaction to proceed to generate a reformed gas by said reformer;
- (c) causing a shift reaction of carbon monoxide in the reformed gas to proceed by a shift converter; and
- (d) counting the number of times of start-up and/or stop of said hydrogen generator including said reformer, said shift converter, and said heater; and
increasing a temperature of the reformed gas flowing in said shift converter and/or increasing a controlled S/C ratio of the reformed gas flowing in said shift converter according to an increase in the counted number of times of start-up and/or stop.

wherein the step (b) includes:

- step (b1) causing the shift reaction to proceed at a first controlled temperature if the counted number of times of start-up and/or stop of said hydrogen generator is less than a predetermined number of times, and

step (b2) causing the shift reaction to proceed at a second controlled temperature higher than the first controlled temperature if the counted number of times of start-up and/or stop of said hydrogen generator is not less than the predetermined number of times.

22. (Currently Amended) The method of operating a hydrogen generator according to claim 21, wherein ~~said hydrogen generator further includes a reformed gas temperature adjusting device configured to cool and heat the reformed gas flowing into said shift converter;~~

~~wherein the increasing of the temperature of the reformed gas is performed by said reformed gas temperature adjusting device~~

in step (b1), the shift reaction is caused to proceed at the first controlled temperature by adjusting a temperature of the reformed gas flowing into said shift converter; and

in step (b2), the shift reaction is caused to proceed at the second controlled temperature by adjusting the temperature of the reformed gas flowing into said shift converter.

23-26. (Cancelled)

27. (Currently Amended) The method of operating a hydrogen generator according to claim 21, wherein ~~the hydrogen generator further includes a reformed gas temperature adjusting device configured to cool and heat the reformed gas flowing into said shift converter;~~ the method further comprising:

(e) counting an accumulated operation time of said hydrogen generator; and
~~controlling said reformed gas temperature adjusting device to increase the temperature of~~

~~the reformed gas according to the increase in the counted number of times of start-up and/or stop-
and an increase in the counted accumulated operation time of said hydrogen generator, wherein~~

the step (b) includes:

(b3) causing the shift reaction to proceed at a third controlled temperature if the
counted accumulated operation time of said hydrogen generator is less than a predetermined
time; and

(b4) causing the shift reaction to proceed at a fourth controlled temperature higher than
the third controlled temperature if the counted accumulated operation time of said hydrogen
generator is not less than the predetermined time.

28. (Cancelled)

29. (Currently Amended) A method of operating a fuel cell system including a ~~hydrogen
generator including a reformer configured to conduct a steam reforming reaction to reform a
material to generate a reformed gas containing carbon monoxide, water and hydrogen; a shift-
converter configured to conduct a shift reaction using the carbon monoxide and steam in the
reformed gas; a water supply device configured to supply the water to said reformer; and a
material feed device configured to feed the material to said reformer; and a fuel cell, the method
comprising:~~

(a) heating a reformer by a heater;

(b) causing a steam reforming reaction to proceed to generate a reformed gas by said
reformer

(c) causing a shift reaction of carbon monoxide in the reformed gas to proceed by a shift converter; and

(d) counting the number of times of start-up and/or stop of said fuel cell system comprising said hydrogen generator including said reformer, said shift converter, and said heater, and a fuel cell;

~~increasing a temperature of the reformed gas flowing in said shift converter and/or a controlled S/C ratio according to an increase in the counted number of times of start-up and/or stop.~~

wherein the step (b) includes

step (b1) causing the shift reaction to proceed at a first controlled temperature if the counted number of times of start-up and/or stop of said fuel cell system is less than a predetermined number of times; and.

step (b2) causing the shift reaction to proceed at a second controlled temperature higher than the first controlled temperature if the counted number of times of start-up and/or stop of said fuel cell system is not less than the predetermined number of times.

30. (Currently Amended) The method of operating a fuel cell system according to Claim 29, ~~wherein said fuel cell system further includes a reformed gas temperature adjusting device configured to cool and heat the reformed gas flowing into said shift converter, the method further comprising:~~

~~wherein the increasing of the temperature of the reformed gas is performed by said reformed gas temperature adjusting device.~~

in step (b1), the shift reaction is caused to proceed at the first controlled temperature by adjusting a temperature of the reformed gas flowing into said shift converter; and

in step (b2), the shift reaction is caused to proceed at the second controlled temperature by adjusting a temperature of the reformed gas flowing into said shift converter.

31-34. (Cancelled)

35. (Currently Amended) The method of operating a fuel cell system according to claim 29, ~~wherein the fuel cell system further includes a reformed gas temperature adjusting device configured to cool and heat the reformed gas flowing into said shift converter; the method further comprising:~~

(c) counting an accumulated operation time of said fuel cell system; and
~~controlling said reformed gas temperature adjusting device to increase the temperature of the reformed gas according to the increase in the counted number of times of start-up and/or stop and an increase in the counted accumulated operation time of said fuel cell system.~~

the step (b) includes:

(b3) causing the shift reaction to proceed at a third controlled temperature if the counted accumulated operation time of said fuel cell system is less than a predetermined time;
and

(b4) causing the shift reaction to proceed at a fourth controlled temperature higher than the third controlled temperature if the counted accumulated operation time of said fuel cell system is not less than the predetermined time.

36. (Cancelled)